

FIXED TWIST-LOCK DIMMING RECEPTACLE (NEMA 7P/5P)

JL-240XHA/XHB      Gold pad narrowed version



JL-240XHA



JL-240HXB



PRODUCT SUMMARY

All the JL-240XH series photocontrol receptacles were designed for the lanterns those intended to have an ANSI C136.10 receptacle to fit a twist-lock photocontrol. This series conform newly published ANSI C136.41 to allow a LED lamp multi-controlled through the receptacle.

This series offers 2 or 4 gold-plated low voltage pads on the top surface to fit photocontrol has ANSI C136.41 conforming spring contacts, and offers 2 or 4 wiring leads at rear side for signal connection.

FEATURES

- Glass-Fiber strongen PBT
- Gilded Pads made from phophor bronze Nickel plated and gilded over 0.7um
- Gold plating per ASTM B 588
- Silicone gasket offered
- Gold pad narrowed for competitive cost

SPECIFICATIONS

Model No.	JL-240XH
Applicable Volt Range	0~480VAC
Rated Frequency	50/60Hz
Load Rating	15A
Signal Control	0-30 VDC, 250 mA Max
Lead	16AWG/14AWG 6" min
Ambient Temperature	-40°C ~ +70°C
Related Humidity	96%
Outdoor Wiring Cable	●
Certifications	ANSI C136.41-2013   CB CE UK CA